



ASTM F2656 M30/P1 (DOS K4/L3)



Designed and used for both perimeter high security and vehicular traffic control. Proven low maintenance, high cyclic/high volume operation, and low cost of ownership. Immobilizes vehicles weighing up to 15,000 lbs. traveling at 30 mph with under 3 feet of penetration. All systems are completely electric (no hydraulics) and are battery backed-up for hundreds of cycles in the event of AC power loss.





Product Specifications The Shield® ASTM F2656 M30/P1 (DOS K4/L3) Model: VPL-CB-24-M30 Full Size Security Gate



DUTY CYCLE:	Continuous.
POWER SUPPLY:	120VAC with 24v DC battery backup. (2) 12v sealed batteries required, NOT included.
POWER MAINTENANCE:	24v built-in battery maintainer keeps batteries charged for built-in battery back-up. "Over-Charge" protection built-in.
CONTROL SYSTEM:	Solid State coated control board.
OPEN / CLOSING CYCLES:	7 – 14 seconds
DELAYED CLOSING:	Adjustable from 0 – 60 seconds.
GATE LENGTHS:	Barrier Arm only - Up to 20' Clear Open With Full Gate Panel: Up to 17' Clear Open. Gates over 8' tall require special shipping & freight arrangements



AutoGate, Inc.
7306 Driver Road - PO Box 50
Berlin Heights, OH 44814
(800) 944-4283

www.AutoGate.com Sales@AutoGate.com