

THE HEARTHROOM SINGLE-SIDED SERIES



TESTED & LISTED TO UL-127, CAN/ULC-S610

Ideal for being placed against a wall, the Hearthroom single-sided wood fireplaces are the perfect fit for any home or cabin. Providing you with an expansive viewing area, supplemental heat, safety you can appreciate, and quality to last a lifetime. Choose from three viewing area sizes: 36", 44" or 48".



Hearthroom 36 SS

- Zero Clearance Fireplace
- Thermostatically Controlled Variable Speed 250 CFM Blower System
- Door Opening: 36"W x 21"H

- 12" ID Round Class A Chimney, 15" OD
- 19" x 19" space required for chimney
- Insulated Panel Dimensions: 47"W x 45"H x 28"D
- Zero Clearance Framing: 51"W x 49"H x 30"D
- 9 1/2" additional space needed for combustion air duct inside wall
- 4" Combustion Air Intake
- Total Weight: 1,000lbs

- Viewing Area: 545 sq in.
- Firebox: 7.5 cubic feet
- Arched or Rectangular front & doors
- Standard black finish
- Minimum Mantel Height: 51 7/8" (measured from the bottom of the unit)
- Max Log Length: 33"



Hearthroom 44 SS

- Zero Clearance Fireplace
- Thermostatically Controlled Variable Speed 250 CFM Blower System
- Door Opening: 44"W x 26"H

- 14" ID Round Class A Chimney, 17" OD
- 21" x 21" space required for chimney
- Insulated Panel Dimensions: 56 1/2"W x 50"H x 28"D
- Zero Clearance Framing: 60 1/2"W x 54"H x 30"D
- 10 1/2" additional space needed for combustion air duct inside wall
- 5" Combustion Air Intake
- Total Weight: 1,200lbs

- Viewing Area: 901 sq in.
- Firebox: 13.2 cubic feet
- Arched or Rectangular front & doors
- Standard black finish
- Minimum Mantel Height: 56 7/8" (measured from the bottom of the unit)
- Max Log Length: 41"



Hearthroom 48 SS

- Zero Clearance Fireplace
- Thermostatically Controlled Variable Speed 250 CFM Blower System
- Door Opening: 48"W x 42"H

- 16" ID Round Class A Chimney, 19" OD
- 23" x 23" space required for chimney
- Insulated Panel Dimensions: 63"W x 66"H x 35 3/4"D
- Zero Clearance Framing: 67"W x 70"H x 37 3/4"D
- 11 1/2" additional space needed for combustion air duct inside wall
- 6" Combustion Air Intake
- Total Weight: 1,700lbs

- Viewing Area: 1,622 sq in.
- Firebox: 24.5 cubic feet
- Arched or Rectangular front & doors
- Standard black finish
- Minimum Mantel Height: 72 15/16" (measured from the bottom of the unit)
- Max Log Length: 45"

THE HEARTHROOM SEE-THROUGH SERIES



TESTED & LISTED TO UL-127, CAN/ULC-S610

Ideal between two adjacent rooms the Hearthroom see-through wood fireplaces are the perfect fit for seamlessly dividing two spaces. Providing you with an expansive viewing area, supplemental heat, safety you can appreciate, and quality to last a lifetime. Choose from three viewing area sizes: 36", 44" or

 Hearthroom 36 ST	■ Zero Clearance Fireplace ■ Thermostatically Controlled Variable Speed 250 CFM Blower System ■ Door Opening: 36"W x 21"H	■ 14" ID Round Class A Chimney, 17" OD ■ 21" x 21" space required for chimney ■ Insulated Panel Dimensions: 51"W x 46"H x 35"D ■ Zero Clearance Framing: 55"W x 50"H x 35"D ■ 9 1/2" additional space needed for combustion air duct inside wall ■ Dual 4" Combustion Air Intakes ■ Total Weight: 1,200lbs	■ Viewing Area: 1,090 sq in. (545 sq in. per side) ■ Firebox: 8.75 cubic feet ■ Arched or Rectangular front & doors ■ Standard black finish ■ Minimum Mantel Height: 51 7/8" (measured from the bottom of the unit) ■ Max Log Length: 33"
 Hearthroom 44 ST	■ Zero Clearance Fireplace ■ Thermostatically Controlled Variable Speed 250 CFM Blower System ■ Door Opening: 44"W x 26"H	■ 16" ID Round Class A Chimney, 19" OD ■ 23" x 23" space required for chimney ■ Insulated Panel Dimensions: 59"W x 50"H x 35"D ■ Zero Clearance Framing: 63"W x 54"H x 35"D ■ 10 1/2" additional space needed for combustion air duct inside wall ■ Dual 5" Combustion Air Intakes ■ Total Weight: 1,400lbs	■ Viewing Area: 1,802 sq in. (901 sq in. per side) ■ Firebox: 13.2 cubic feet ■ Arched or Rectangular front & doors ■ Standard black finish ■ Minimum Mantel Height: 56 7/8" (measured from the bottom of the unit) ■ Max Log Length: 41"
 Hearthroom 48 ST	■ Zero Clearance Fireplace ■ Thermostatically Controlled Variable Speed 250 CFM Blower System ■ Door Opening: 48"W x 42 1/2"H	■ 18" ID Round Class A Chimney, 21" OD ■ 25" x 25" space required for chimney ■ Insulated Panel Dimensions: 63"W x 66 1/2"H x 42 1/2"D ■ Zero Clearance Framing: 67"W x 70 1/2"H x 42 1/2"D ■ 11 1/2" additional space needed for combustion air duct inside wall ■ Dual 6" Combustion Air Intakes ■ Total Weight: 1,900lbs	■ Viewing Area: 3,244 sq in. (1,622 sq in. per side) ■ Firebox: 24.5 cubic feet ■ Arched or Rectangular front & doors ■ Standard black finish ■ Minimum Mantel Height: 72 15/16" (measured from the bottom of the unit) ■ Max Log Length: 45"

THE HEARTHROOM INDOOR/OUTDOOR SERIES



TESTED & LISTED TO UL-127, CAN/ULC-S610

Our most popular option, our indoor/outdoor Hearthroom wood fireplaces are perfect for entertaining indoors and out. Keep the mess out of your home by loading wood from the exterior side while enjoying the ambiance from the interior side. Choose from three viewing area sizes: 36", 44" or 48".



Hearthroom 36 IO

- Zero Clearance Fireplace
- Thermostatically Controlled Variable Speed 250 CFM Blower System
- Door Opening: 36"W x 21"H

- 14" ID Round Class A Chimney, 17" OD
- 21" x 21" space required for chimney
- Insulated Panel Dimensions: 51"W x 46"H x 35"D
- Zero Clearance Framing: 55"W x 50"H x 35"D
- 9 1/2" additional space needed for combustion air duct inside wall
- Dual 4" Combustion Air Intakes
- Total Weight: 1,300lbs

- Viewing Area: 1,090 sq in. (545 sq in. per side)
- Firebox: 8.75 cubic feet
- Arched or Rectangular front & doors
- Standard black finish
- Minimum Mantel Height: 51 7/8" (measured from the bottom of the unit)
- Max Log Length: 33"



Hearthroom 44 IO

- Zero Clearance Fireplace
- Thermostatically Controlled Variable Speed 250 CFM Blower System
- Door Opening: 44"W x 26"H

- 16" ID Round Class A Chimney, 19" OD
- 23" x 23" space required for chimney
- Insulated Panel Dimensions: 59"W x 50"H x 35"D
- Zero Clearance Framing: 63"W x 54"H x 35"D
- 10 1/2" additional space needed for combustion air duct inside wall
- Dual 5" Combustion Air Intakes
- Total Weight: 1,400lbs

- Viewing Area: 1,802 sq in. (901 sq in. per side)
- Firebox: 13.2 cubic feet
- Arched or Rectangular front & doors
- Standard black finish
- Minimum Mantel Height: 56 7/8" (measured from the bottom of the unit)
- Max Log Length: 41"



Hearthroom 48 IO

- Zero Clearance Fireplace
- Thermostatically Controlled Variable Speed 250 CFM Blower System
- Door Opening: 48"W x 42"H

- 18" ID Round Class A Chimney, 21" OD
- 25" x 25" space required for chimney
- Insulated Panel Dimensions: 63"W x 66 1/2"H x 42 1/2"D
- Zero Clearance Framing: 67"W x 70 1/2"H x 42 1/2"D
- 11 1/2" additional space needed for combustion air duct inside wall
- Dual 6" Combustion Air Intakes
- Total Weight: 1,600lbs

- Viewing Area: 3,244 sq in. (1,622 sq in. per side)
- Firebox: 24.5 cubic feet
- Arched or Rectangular front & doors
- Standard black finish
- Minimum Mantel Height: 72 15/16" (measured from the bottom of the unit)
- Max Log Length: 45"